NSN 5930-01-033-2774



Pressure Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-01-033-2774
Inside Diameter:
0.250 inches single connection
Thread Length:
1.750 inches single pressure connection and 2.688 inches single pressure connection
Overall Length:
3.250 inches
Overall Height:
7.313 inches
Overall Width:
2.563 inches
Body Height:
4.625 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Longest Horizontal Distance Between Mounting Centers:
1.625 inches
Longest Vertical Distance Between Mounting Centers:
1.375 inches
Pressure Switch Type:
Differential
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+250.00 actuation point pounds per square inch and -3.00/+220.00 deactuation point pounds per square inch

NSN 5930-01-033-2774

Pressure Switch - Page 2 of 2



0	A -1		T	
Contact	Aa	justment	Ιy	pe:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0