NSN 5930-01-033-5366

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-033-5366

Thread Class: 2a single mounting facility **Thread Length:** 0.750 inches single mounting facility **Overall Length:** 3.751 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Shaft Length:** 1.313 inches single actuator **Individual Section Quantity: Knob Manufacturer Code:** 75282 **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Cam actuated and actuator knob Thready Qty Per Inch (tpi): 14 single mounting facility **Thread Size:** 0.750 inches single mounting facility **Contact Voltage Rating In Volts:** 250.0 highest ac voltage rating at sea level **Cam Actuated Switch Contact Arrangement:** 4 two circuit, double break/double make, one position momentary single switch single section in-line **Switch Actuator Indexing Position Quantity:** 2 single actuator Shaft Type: Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.250 inches single actuator **Terminal Type:** Tab, solder lug **Contact Load Current Rating:**

Style Designator:

In-line, cam actuated

5.0 amperes resistive load highest ac voltage rating at sea level

NSN 5930-01-033-5366

Rotary Switch - Page 2 of 2



	T	hr	ead	Series	Design	nator
--	---	----	-----	---------------	--------	-------

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0