

View Online at <https://aerobasegroup.com/nsn/5930-01-033-7917>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

Body Length:

Between 1.079 inches and 1.109 inches

Body Width:

0.400 inches

Body Height:

Between 0.610 inches and 0.640 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.116 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Width:

0.165 inches

Actuator Free Position Height:

Between 0.563 inches and 0.593 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

End Application:

Dehydrator fltr dsc 84147

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 14.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0