NSN 5930-01-033-9135

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-033-9135

Hannadava I anationalamvinammental Dustration.
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length: 11.751 inches
Overall Height:
6.750 inches
Overall Width:
6.750 inches
First Flat Length:
1.375 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.688 inches single actuator
Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
5.625 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
4 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
28.0 dc at sea level
Mounting Facility Pattern:

mounting racinty rattern

Four position rectangular single mounting facility

NSN 5930-01-033-9135

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
200.0 amperes resistive load ac at sea level
Precious Material And Location:
Contact surface silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0