

NSN 5930-01-033-9135 Rotary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-01-033-9135
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
11.751 inches
Overall Height:
6.750 inches
Overall Width:
6.750 inches
First Flat Length:
1.375 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.688 inches single actuator
Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
5.625 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
4 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

NSN 5930-01-033-9135

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surface silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0