NSN 5930-01-033-9136

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

3 quick disconnect, female



View Online at https://aerobasegroup.com/nsn/5930-01-033-9136

Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.375 inches
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Length:
0.094 inches
Actuator Style:
Rectangular
Actuator Height:
0.049 inches
Actuator Width:
0.094 inches
Actuator Free Position Height:
Actuator Fee Feeting II.
0.330 inches
0.330 inches
0.330 inches Maximum Voltage Rating In Volts:
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type:
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method:
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force:
Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams
0.330 inches Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams Switch Actuating Force:
Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams Switch Actuating Force: 90.0 grams
Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams Switch Actuating Force: 90.0 grams Actuator Movement:
Maximum Voltage Rating In Volts: 125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams Switch Actuating Force: 90.0 grams Actuator Movement: Between 0.030 pretravel inches and 0.035 overtravel inches and 0.004 differential inches

NSN 5930-01-033-9136

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0