## NSN 5930-01-033-9136

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

3 quick disconnect, female



View Online at https://aerobasegroup.com/nsn/5930-01-033-9136

Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.375 inches
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Length:
0.094 inches
Actuator Style:
Rectangular
Actuator Height:
0.049 inches
Actuator Width:
0.094 inches
A A CASE OF THE SECOND STATE OF THE SECOND STA
Actuator Free Position Height:
0.330 inches
0.330 inches
0.330 inches  Maximum Voltage Rating In Volts:
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac  Inclosure Type:
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac  Inclosure Type:  Fully enclosed
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed Mounting Method:
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac  Inclosure Type:  Fully enclosed  Mounting Method:  Unthreaded hole  Nonpile-up Contact Arrangement:
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac  Inclosure Type:  Fully enclosed  Mounting Method:  Unthreaded hole  Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed  Mounting Method: Unthreaded hole  Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit  Switch Release Force:
Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams
0.330 inches  Maximum Voltage Rating In Volts:  125.0 ac  Inclosure Type:  Fully enclosed  Mounting Method:  Unthreaded hole  Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit  Switch Release Force:  15.0 grams  Switch Actuating Force:
Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams Switch Actuating Force: 90.0 grams
Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams Switch Actuating Force: 90.0 grams Actuator Movement:
Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 15.0 grams Switch Actuating Force: 90.0 grams Actuator Movement: Between 0.030 pretravel inches and 0.035 overtravel inches and 0.004 differential inches

## NSN 5930-01-033-9136

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0