NSN 5930-01-033-9669

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-033-9669
Overall Length:
7.594 inches
Overall Height:
3.875 inches
Overall Width:
4.250 inches
Body Length:
4.250 inches
Body Height:
3.875 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
3.000 inches
Longest Vertical Distance Between Mounting Centers:
3.625 inches
Pressure Switch Type:
Differential
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
350.00 pounds per square inch gage
Thread Size:
0.250 inches all pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+70.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut and internal deactuation point hex nut

NSN 5930-01-033-9669

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0