

View Online at <https://aerobasegroup.com/nsn/5930-01-033-9671>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.376 inches

Overall Height:

2.906 inches

Overall Width:

2.813 inches

Shaft Length:

2.438 inches single actuator

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

2

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

H

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contact surface silver and terminal surface silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0