

View Online at <https://aerobasegroup.com/nsn/5930-01-033-9671>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.376 inches

**Overall Height:**

2.906 inches

**Overall Width:**

2.813 inches

**Shaft Length:**

2.438 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.221 inches single mounting facility

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

H

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.188 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Precious Material And Location:**

Contact surface silver and terminal surface silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0