## NSN 5930-01-034-0432

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-034-0432
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.998 inches and 1.002 inches
Body Length:
Between 1.925 inches and 1.955 inches
Body Width:
Between 0.675 inches and 0.705 inches
Body Height:
0.105 inches
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.143 inches
Actuator Length:
2.500 inches
Actuator Style:
Leaf
Actuator Width:
Between 0.175 inches and 0.205 inches
Actuator Free Position Height:
Between 0.660 inches and 0.780 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Uninclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
21.0 grams
Switch Actuating Force:
85.0 grams
Actuator Movement:
Between 0.380 pretravel inches and 0.160 overtravel inches and 0.125 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 20.000 amperes resistive ac
Terminal Type And Quantity:
3 screw and 3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## **NSN 5930-01-034-0432** Sensitive Switch - Page 2 of 2



Fiig:

A053a0