## NSN 5930-01-034-1899

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-034-1899

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
5.376 inches
Overall Height:
2.813 inches
Overall Width:
2.813 inches
Shaft Length:
2.438 inches single actuator
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
С
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
<b>Shortest Horizontal Distance Between Mounting Centers:</b>
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
1 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
1 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator

## **NSN 5930-01-034-1899** Rotary Switch - Page 2 of 2



Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load highest ac voltage rating at sea level
Special Features:
Escutcheon plate included
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0