NSN 5930-01-034-1900

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-034-1900

Hazardous Locations/environmental Protection:
Explosion proof
Overall Height:
2.906 inches
Overall Width:
2.813 inches
Shaft Length:
2.438 inches single actuator
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
Н
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
3 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:

oquare orian oize.

0.250 inches single actuator

NSN 5930-01-034-1900Rotary Switch - Page 2 of 2



Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0