NSN 5930-01-034-4880

Pressure Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5930-01-034-4000
Thread Class:
2a single threaded bushing
Inside Diameter:
0.250 inches single connection
Overall Length:
5.000 inches
Overall Height:
2.813 inches
Overall Width:
1.562 inches
Body Length:
3.812 inches
Pressure Switch Type:
Gage
Mounting Method:
Threaded bushing
Contact Action Stimulus:
Increase
Proof Pressure:
6000.00 pounds per square inch gage
Thread Size:
1.000 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
50.0 milliamperes resistive load sixth voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+581.00/+4800.00 actuation point pounds per square inch gage and +240.00/+4459.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
External actuation point screw and external deactuation point screw
Contact Voltage Rating In Volts:
600.0 ac at sea level fourth voltage
Pressure Connector Type:
Plain, threaded internal single connection
Frequency In Hertz:

Gas

60.0 third voltage

Media For Which Designed:

NSN 5930-01-034-4880

Pressure Switch - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

Bourdon tube, open frame

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0