

View Online at <https://aerobasegroup.com/nsn/5930-01-034-4880>

Thread Class:

2a single threaded bushing

Inside Diameter:

0.250 inches single connection

Overall Length:

5.000 inches

Overall Height:

2.813 inches

Overall Width:

1.562 inches

Body Length:

3.812 inches

Pressure Switch Type:

Gage

Mounting Method:

Threaded bushing

Contact Action Stimulus:

Increase

Proof Pressure:

6000.00 pounds per square inch gage

Thread Size:

1.000 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

50.0 milliamperes resistive load sixth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+581.00/+4800.00 actuation point pounds per square inch gage and +240.00/+4459.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Style Designator:

Bourdon tube, open frame

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0