

View Online at <https://aerobasegroup.com/nsn/5930-01-034-8124>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.469 inches

Body Length:

0.562 inches

Body Width:

0.546 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Aircraft, ac-130h, mc-130h, ec-130e, hc-130); tarawa class lha; helicopter, search and rescue, hh-60h; landing craft air cushion (lcac); aircraft, c-2a (reprocured); helicopter, uscg search and rescue, hh-60j; helicopter, carrier based asw, sh-60f; helicopter, mh-53e; helicopter, advance attack, ah-1w; ticonderoga class cg (47)

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary, two positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0