NSN 5930-01-035-0935

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-035-0935

Overall Length: 1.023 inches Overall Height: 0.232 inches Overall Width: 0.440 inches Individual Section Quantity: 7 Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A052b0	
Overall Height: 0.232 inches Overall Width: 0.440 inches Individual Section Quantity: 7 Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Overall Length:
Overall Width: 0.440 inches Individual Section Quantity: 7 Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.023 inches
Overall Width: 0.440 inches Individual Section Quantity: 7 Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Overall Height:
0.440 inches Individual Section Quantity: 7 Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.232 inches
Individual Section Quantity: 7 Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Overall Width:
Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.440 inches
Contact Voltage Rating In Volts: 28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Individual Section Quantity:
28.0 dc at sea level Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	7
Cam Actuated Switch Contact Arrangement: 6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Contact Voltage Rating In Volts:
6 pole, single throw, both positions maintained each switch single section in-line Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	28.0 dc at sea level
Contact Switching Action: Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cam Actuated Switch Contact Arrangement:
Breaks before makes single section in-line Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	6 pole, single throw, both positions maintained each switch single section in-line
Contact Load Current Rating: 125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Contact Switching Action:
125.0 amperes resistive load dc at sea level Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Breaks before makes single section in-line
Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Contact Load Current Rating:
In-line, cam actuated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	125.0 amperes resistive load dc at sea level
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	In-line, cam actuated
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A052b0	Fiig:
	A052b0