

View Online at <https://aerobasegroup.com/nsn/5930-01-035-1785>

**Thread Length:**

0.235 inches single mounting facility and 0.265 inches single mounting facility

**Overall Length:**

Between 1.302 inches and 1.432 inches

**Overall Diameter:**

Between 0.485 inches and 0.515 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level

**Special Features:**

30 volts dc resistive load; shaft is flat opposite contacting position of pole no. 1; adjustable stop switches; shaft, stop arm, washer, ring and detent balls are 302 stainless steel; bushing and mounting nut are brass, cadmium plated; stop pins 303 stainless steel; 36 degree angle of throw; 2 non-shorting poles; shaft length is 0.281

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0