

View Online at <https://aerobasegroup.com/nsn/5930-01-035-1931>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.373 inches and 0.377 inches

**Body Length:**

Between 0.771 inches and 0.791 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.349 inches and 0.369 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Switch Actuator Quantity:**

1

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive dc and 5.000 amperes inductive ac and 1.500 amperes lamp ac and 5.000 amperes resistive ac

**Specification Data:**

80249-mil-s-8805/2 government specification and 80249-mil-s-8805 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0