NSN 5930-01-035-5181

Rotary Switch Section - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-035-5181

Overall Diameter:

1.344 inches

Body Thickness:

Between 0.060 inches and 0.064 inches

Unthreaded Mounting Hole Diameter:

0.089 inches single mounting facility and 0.093 inches single mounting facility

Distance Between Mounting Facility Centers:

0.807 inches single mounting facility and 0.817 inches single mounting facility

Operating Tempurature Range:

-55.0/+25.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

10 single section rear

Mounting Method:

Strut single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Mounting Facility Pattern:

Two position in-line single mounting facility

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Switch section, rotary

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5930-01-035-5181

Rotary Switch Section - Page 2 of 2

Fiig: A052b0

