

View Online at <https://aerobasegroup.com/nsn/5930-01-035-6822>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

1.094 inches

**Body Width:**

0.385 inches

**Body Height:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.188 inches

**Actuator Height:**

0.250 inches

**Actuator Free Position Height:**

0.047 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

1whidbey island class lsd, sirius class t-afs 8, forrestal class cv, wasp class lhd, austin ship class lpd-4 amphibious transport docks, mars class t-afs 1, supply class aoe, waters class tags-45, usns henery j. Kaiser class tao. Boat davits.

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

5.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

Between 7.0 ounces and 12.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.002 differential inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes motor dc and 10.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0