

View Online at <https://aerobasegroup.com/nsn/5930-01-035-7137>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

7.969 inches

Overall Height:

3.688 inches

Overall Width:

3.375 inches

First Flat Length:

0.875 inches single actuator

Flat Height:

0.325 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.250 inches single actuator

Unthreaded Mounting Hole Diameter:

0.344 inches single mounting facility

Individual Section Quantity:

10

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

A

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

4 single section periphery

Mounting Facility Circle Radius:

1.609 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks single section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0