

View Online at <https://aerobasegroup.com/nsn/5930-01-035-7451>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and salt spray resistant and shock proof

Bushing Length:

0.468 inches

Body Length:

1.336 inches

Body Width:

0.734 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Control unit 06481

Mounting Surface To Terminal End Distance:

1.203 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0