

View Online at <https://aerobasegroup.com/nsn/5930-01-035-9456>

**Body Length:**

3.109 inches

**Body Width:**

1.500 inches

**Body Height:**

1.344 inches

**Actuator Style:**

Round

**Actuator Height:**

0.375 inches

**Actuator Adapter Style:**

Pushbutton

**Adapter Bushing Length:**

1.000 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

4 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes inductive dc and 4.000 amperes resistive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc

**Special Features:**

Altitude-sea level to 50000 ft.; operating cycles 25000 min; difference of operating & reset point between poles 0.015max; 2 5/8-24nef 2b hex nuts 0.812 across flats x 0.125 thk; internal tooth lockwasher 0.875 o.D.X0.22 thk; keying washer 7/8 o.D.X 0.040 thk tab 0.110 wd; 2-0.037 diameter holes for wire lockin (one in each hex nut) ; switch resistant to skydrol 500a, jp4 & kerosene; internal wiring no.20 gage

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0