

View Online at <https://aerobasegroup.com/nsn/5930-01-035-9456>

Body Length:

3.109 inches

Body Width:

1.500 inches

Body Height:

1.344 inches

Actuator Style:

Round

Actuator Height:

0.375 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

1.000 inches

Maximum Voltage Rating In Volts:

28.0 dc

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

4 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes inductive dc and 4.000 amperes resistive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc

Special Features:

Altitude-sea level to 50000 ft.; operating cycles 25000 min; difference of operating & reset point between poles 0.015max; 2 5/8-24nef 2b hex nuts 0.812 across flats x 0.125 thk; internal tooth lockwasher 0.875 o.D.X0.22 thk; keying washer 7/8 o.D.X 0.040 thk tab 0.110 wd; 2-0.037 diameter holes for wire lockin (one in each hex nut) ; switch resistant to skydrol 500a, jp4 & kerosene; internal wiring no.20 gage

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0