

View Online at <https://aerobasegroup.com/nsn/5930-01-036-7986>

**Distance Between Mounting Facility Centers:**

2.187 inches

**Capillary Tube Length:**

44.0 inches

**Temperature Sensing Element Type:**

Capillary tube

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

25.0 amperes inductive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+25.00/+44.00 actuation point degrees fahrenheit and +25.00/+44.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

38.00 actuation point degrees fahrenheit and 35.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

240.0 ac at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0