

View Online at <https://aerobasegroup.com/nsn/5930-01-036-8847>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

2.300 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.850 inches single actuator

**Overall Diameter:**

1.000 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**End Application:**

Hayes class t-ag 195, sturgeon class ssn (637), sirius class t-afs 8, ticonderoga class cg (47), nimitz class cvn, los angeles class ssn (688), austin ship class lpd-4 amphibious transport docks, forrestal class cv, virginia class cgn (41), spruance class dd (963)

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contact and rotor blade surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0