NSN 5930-01-037-0534

Sensitive Switch - Page 1 of 1

No Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-01-037-0534 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Watertight **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.190 inches **Body Length:** 0.620 inches **Body Width:** 0.320 inches **Unthreaded Mounting Hole Diameter:** 0.090 inches **Actuator Style:** Round **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** Between 5.0 ounces and 17.0 ounces **Actuator Movement:** Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**