NSN 5930-01-037-0937

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-037-0937

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.781 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

First Flat Length:

0.750 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.125 inches single actuator

Individual Section Quantity:

7

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

А

Longest Horizontal Distance Between Mounting Centers:

1.641 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.641 inches single mounting facility

End Application:

Ohio class ssn ship (trident), trident outfitting and furnishings, moored training ship, submarine auxiliary and miscellaneous systems, seawolf class ssn, submarine engineering and diesel s.

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

NSN 5930-01-037-0937

Rotary Switch - Page 2 of 2



Contact Voltage Rating In Volts: 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round, square, threaded hole single actuator **Criticality Code Justification:** Feat Square Shaft Size: 0.219 inches single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level **Special Features:** Weapon system essential **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0