

View Online at <https://aerobasegroup.com/nsn/5930-01-037-0970>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

4.146 inches

Overall Height:

1.531 inches

Overall Width:

1.406 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.751 inches 2nd actuator

Individual Section Quantity:

5

Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 2nd actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Clip

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Detent Rotational Torque Range:

+17.000/+33.000 inch-ounces 1st actuator

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0