

View Online at <https://aerobasegroup.com/nsn/5930-01-037-0972>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Salt spray resistant

**Overall Length:**

2.125 inches

**Shaft Diameter:**

0.375 inches 1st actuator

**Shaft Length:**

0.875 inches 2nd actuator

**Nonturn Device Radius:**

0.531 inches at 11:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 11:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

7 2nd section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.625 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

18 all actuators

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Clip

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

20.0 degrees all actuators

**Detent Rotational Torque Range:**

+15.000/+35.000 inch-ounces all actuators

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Clip surface gold and clips silver and rotor blades silver

**Precious Material:**

Gold and silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0