

View Online at <https://aerobasegroup.com/nsn/5930-01-037-3499>

Inside Diameter:

0.125 inches all connections

Overall Length:

7.876 inches

Overall Height:

2.875 inches

Overall Width:

5.250 inches

Body Length:

2.500 inches

Body Width:

4.875 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 all pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

60.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+8.00/+55.00 actuation point pounds per square inch and +5.00/+75.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0