

View Online at <https://aerobasegroup.com/nsn/5930-01-037-4279>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

4.938 inches

**Overall Height:**

5.125 inches

**Overall Width:**

2.875 inches

**Body Length:**

4.625 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

1.750 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 580.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.375 inches single pressure connection

**Mounting Facility Pattern:**

Obtuse triangle

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Sensing Element Burst Pressure:**

216.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

9.6 amperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0