

View Online at <https://aerobasegroup.com/nsn/5930-01-037-4289>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Bushing Length:**

0.250 inches

**Body Length:**

0.900 inches

**Body Width:**

0.400 inches

**Body Height:**

1.000 inches

**Actuator Diameter:**

0.150 inches

**Actuator Height:**

0.090 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Used on sentry f22 aircraft

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.250 amperes resistive ac

**Special Features:**

0.031 in. Wide, 0.031 in. Deep slot for screw driver actuation

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0