NSN 5930-01-037-6222

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Explosion proof
Overall Length:
3.406 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches

First Flat Length:



View Online at https://aerobasegroup.com/nsn/5930-01-037-6222

0.750 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.875 inches single actuator
Unthreaded Mounting Hole Diameter:
1.156 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section periphery
Throw Quantity:
2 each section periphery
Mounting Facility Circle Radius:
0.221 inches single mounting facility
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator

NSN 5930-01-037-6222Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0