

View Online at <https://aerobasegroup.com/nsn/5930-01-037-6226>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

3.137 inches

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

1.200 inches 1st actuator

**Nonturn Device Radius:**

0.531 inches at 10:00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Pin at 10:00 o'clock

**End Application:**

Los angeles class ssn (688), oliver perry class ffg, ticonderoga class cg (47), virginia class cgn (41), spruance class dd (963), arleigh burke class ddg, wasp class lhd, forrestal class cv, tarawa class lha, kidd class ddg

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

1 3rd section front

**Throw Quantity:**

6 3rd section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

12 all actuators

**Shaft Type:**

Round, hollowed 1st actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 3rd section rear

**Switch Actuator Positioning Increment:**

30.0 degrees all actuators

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Internal clips silver and internal rotor blades silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0