

View Online at <https://aerobasegroup.com/nsn/5930-01-037-6226>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

3.137 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

1.200 inches 1st actuator

Nonturn Device Radius:

0.531 inches at 10:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Pin at 10:00 o'clock

End Application:

Los angeles class ssn (688), oliver perry class ffg, ticonderoga class cg (47), virginia class cgn (41), spruance class dd (963), arleigh burke class ddg, wasp class lhd, forrestal class cv, tarawa class lha, kidd class ddg

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 3rd section front

Throw Quantity:

6 3rd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

12 all actuators

Shaft Type:

Round, hollowed 1st actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 3rd section rear

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Special Features:

Weapon system essential

Precious Material And Location:

Internal clips silver and internal rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0