

View Online at <https://aerobasegroup.com/nsn/5930-01-037-6230>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and corrosion resistant

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.250 inches

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

1.500 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.320 inches

Housing Height:

1.780 inches

Housing Length:

2.840 inches

Housing Width:

1.650 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

0.800 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.342 inches

Maximum Voltage Rating In Volts:

110.0 ac and 115.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

50.0 pretravel degrees and 15.0 overtravel degrees and 15.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0