

View Online at <https://aerobasegroup.com/nsn/5930-01-037-6231>

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Actuator Length:**

2.200 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

1.016 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.187 inches

**Housing Height:**

1.218 inches

**Housing Length:**

2.125 inches

**Housing Width:**

1.438 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.840 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

160.0 inch-ounces

**Switch Actuating Force:**

320.0 inch-ounces

**Actuator Movement:**

Between 27.0 pretravel degrees and 27.0 overtravel degrees and 10.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0