

View Online at <https://aerobasegroup.com/nsn/5930-01-037-6231>

Hazardous Locations/environmental Protection:

Corrosion resistant

Actuator Length:

2.200 inches

Actuator Style:

Roller arm

Actuator Height:

1.016 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.187 inches

Housing Height:

1.218 inches

Housing Length:

2.125 inches

Housing Width:

1.438 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.840 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

160.0 inch-ounces

Switch Actuating Force:

320.0 inch-ounces

Actuator Movement:

Between 27.0 pretravel degrees and 27.0 overtravel degrees and 10.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0