NSN 5930-01-037-6645

Rotary Switch - Page 1 of 2

Thread Class:

Overall Length:

2b single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-01-037-6645

2.885 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.125 inches single actuator **Individual Section Quantity:** 3 **Longest Horizontal Distance Between Mounting Centers:** 1.375 inches single mounting facility **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 each section rear **Throw Quantity:** 2 each section rear **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, flatted single actuator

NSN 5930-01-037-6645Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load dc at sea level
Precious Material And Location:
Contact surface gold and terminals silver
Precious Material:
Gold and silver
Style Designator:
Tap, square frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0