

View Online at <https://aerobasegroup.com/nsn/5930-01-037-9697>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and moisture resistant and salt spray resistant and sand proof and shock resistant and vibration resistant

Bushing Length:

Between 0.160 inches and 0.180 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.090 inches and 0.096 inches

Actuator Height:

Between 0.625 inches and 0.675 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.749 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

Special Features:

Internal tooth lockwasher, nut and silicone seal included on mtg bushing

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0