

View Online at <https://aerobasegroup.com/nsn/5930-01-038-0574>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.936 inches

Overall Height:

0.750 inches

Overall Width:

0.656 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.094 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.304 inches

Actuator Length:

0.156 inches

Actuator Style:

Rectangular

Actuator Height:

0.180 inches

Actuator Width:

0.156 inches

Actuator Free Position Height:

0.274 inches

Maximum Voltage Rating In Volts:

230.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

0.440 pretravel inches and 0.062 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0