NSN 5930-01-038-0574

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-038-0574

Hele meaning a
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.936 inches
Overall Height:
0.750 inches
Overall Width:
0.656 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.094 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.304 inches
Actuator Length:
0.156 inches
Actuator Style:
Rectangular
Actuator Height:
0.180 inches
Actuator Width:
0.156 inches
0.156 inches Actuator Free Position Height:
Actuator Free Position Height:
Actuator Free Position Height: 0.274 inches
Actuator Free Position Height: 0.274 inches Maximum Voltage Rating In Volts:
Actuator Free Position Height: 0.274 inches Maximum Voltage Rating In Volts: 230.0 ac
Actuator Free Position Height: 0.274 inches Maximum Voltage Rating In Volts: 230.0 ac Inclosure Type:

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch unit

NSN 5930-01-038-0574 Sensitive Switch - Page 2 of 2



Switch Release Force:	
3.0 ounces	
Switch Actuating Force:	
20.0 ounces	
Actuator Movement:	
0.440 pretravel inches and 0.062 overtravel inches and 0.005 differential inches	
Contact Load Current Rating At Maximum Rated Voltage:	
10.000 amperes resistive ac	
Precious Material And Location:	
Contacts silver	
Terminal Type And Quantity:	
4 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A053a0	