## NSN 5930-01-038-0706

Rotary Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-038-0706

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

**Overall Length:** 

1.837 inches

First Flat Length:

0.328 inches single actuator

Flat Height:

0.095 inches single actuator

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.625 inches single actuator

**Overall Diameter:** 

0.641 inches

**Individual Section Quantity:** 

2

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

4 1st section front

**Throw Quantity:** 

2 each section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

60.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-01-038-0706

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load dc at sea level

**Style Designator:** 

Tap, circular, bushing mount

**Thread Series Designator:** 

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0