

View Online at <https://aerobasegroup.com/nsn/5930-01-038-1614>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.765 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.469 inches

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.781 inches 2nd actuator

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

3 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

3 1st actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

30.0 degrees 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

750.0 milliamperes resistive load ac at sea level

**Special Features:**

Second actuates variable resistor

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0