

View Online at <https://aerobasegroup.com/nsn/5930-01-038-3091>

Thread Class:

3b single pressure connection

Inside Diameter:

0.375 inches single connection

Overall Length:

4.875 inches

Overall Height:

2.875 inches

Overall Width:

2.750 inches

Body Height:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

60.00 inches of water

Thread Size:

0.375 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

3.2 amperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+8.00/+55.00 actuation point inches of water and +5.00/+47.00 deactuation point inches of water

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0