

View Online at <https://aerobasegroup.com/nsn/5930-01-038-4683>

Thread Class:

3b all threaded hole

Thread Length:

0.188 inches all threaded hole

Overall Length:

3.850 inches

Overall Width:

3.280 inches

Body Length:

3.500 inches

Longest Horizontal Distance Between Mounting Centers:

2.820 inches

Longest Vertical Distance Between Mounting Centers:

2.812 inches

Pressure Switch Type:

Differential

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Thread Size:

0.190 inches all threaded hole

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

6 pole, double throw, two positions momentary

Contact Load Current Rating:

3.0 amperes inductive load single voltage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Special Features:

Nairspeed actuation increasing by 245 knots, decreasing at 218 knots; low altitude actuation increasing & decreasing at 15000 plus or minus 1000 ft; high altitude actuation increasing at 30000 plus or minus 1500 ft, decreasing by 25000 ft; pitot port pressure operating 0-21 in.Hg diff., overload 29-60 in.Hga; static port pressure operating 2-30 in.Hga, overload 1-40 in.Hga; operating temp minus 65 to plus 160 degrees f; non-operating temp minus 80 to plus 160 degrees f; weight-2.5 lbs

Media For Which Designed:

Gas

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0