## NSN 5930-01-038-5453

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-038-5453

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.375 inches single mounting facility

**Overall Length:** 

3.901 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.380 inches single actuator

**Individual Section Quantity:** 

5

**End Application:** 

Command control and communication system 427m.

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 5th section front

**Throw Quantity:** 

3 1st section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 4th section

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

**Shaft Type:** 

Round single actuator

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Clip and printed circuit

**Contact Switching Action:** 

Makes before breaks 5th section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-01-038-5453

Rotary Switch - Page 2 of 2



Contact Load Current Rating
-----------------------------

500.0 milliamperes resistive load ac at sea level

**Special Features:** 

Weapon system essential

**Precious Material And Location:** 

Clips and rotor blade surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0