# NSN 5930-01-038-5460

Sensitive Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-038-5460

# Body Style:

Hole mounted

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

# Body Length:

1.250 inches

#### **Body Width:**

0.491 inches

# Body Height:

1.310 inches

#### **Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:** 

#### 0.114 inches

#### Actuator Length:

## 0.250 inches

Actuator Style:

Rectangular

## Actuator Height:

0.125 inches

#### Actuator Width:

0.296 inches

## **Actuator Free Position Height:**

0.505 inches

## Actuator Adapter Style:

Pushbutton

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Inclosure Type:

Fully enclosed

## Nonpile-up Contact Arrangement:

3 two circuit, double break/double make, one position momentary single switch unit

#### Switch Release Force:

6.0 ounces

#### Switch Actuating Force:

40.0 inch-ounces

#### **Actuator Movement:**

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.035 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes motor dc and 15.000 amperes resistive ac and 15.000

amperes inductive ac and 6.000 amperes motor ac

## Special Features:

Actuator adapter has red pushbutton



# NSN 5930-01-038-5460

Sensitive Switch - Page 2 of 2



# Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0